



„Chemicals are added to the water to facilitate the underground fracturing process that releases natural gas. Fracturing fluid is primarily water and approximately 0.5% chemical additives (friction reducer, agents countering rust, agents killing microorganism). Since (depending on the size of the area) millions of liters of water are used, this means that hundreds of thousands liters of chemicals are often injected into the soil. Only about 50% to 70% of the resulting volume of contaminated water is recovered and stored in above-ground ponds to await removal by tanker. The remaining "produced water" is left in the earth where it can lead to contamination of groundwater aquifers, though the industry deems this "highly unlikely".

4. „Chemicals are added to the water to facilitate the underground fracturing process that releases natural gas. Fracturing fluid is primarily water and approximately 0.5% chemical additives (friction reducer, agents countering rust, agents killing microorganism). Since (depending on the size of the area) millions of liters of water are used, this means that hundreds of thousands liters of chemicals are often injected into the soil. Only about 50% to 70% of the resulting volume of contaminated water is recovered and stored in above-ground ponds to await removal by tanker. The remaining "produced water" is left in the earth where it can lead to contamination of groundwater aquifers, though the industry deems this "highly unlikely".

5. „Chemicals are added to the water to facilitate the underground fracturing process that releases natural gas. Fracturing fluid is primarily water and approximately 0.5% chemical additives (friction reducer, agents countering rust, agents killing microorganism). Since (depending on the size of the area) millions of liters of water are used, this means that hundreds of thousands liters of chemicals are often injected into the soil. Only about 50% to 70% of the resulting volume of contaminated water is recovered and stored in above-ground ponds to await removal by tanker. The remaining "produced water" is left in the earth where it can lead to contamination of groundwater aquifers, though the industry deems this "highly unlikely".

6. „Chemicals are added to the water to facilitate the underground fracturing process that releases natural gas. Fracturing fluid is primarily water and approximately 0.5% chemical additives (friction reducer, agents countering rust, agents killing microorganism). Since (depending on the size of the area) millions of liters of water are used, this means that hundreds of thousands liters of chemicals are often injected into the soil. Only about 50% to 70% of the resulting volume of contaminated water is recovered and stored in above-ground ponds to await removal by tanker. The remaining "produced water" is left in the earth where it can lead to contamination of groundwater aquifers, though the industry deems this "highly unlikely".

